



**STANDARD  
PRESSURE**

IDEAL FOR USE WITH  
AUTO NOZZLE  
METER



# GPI > Fuel Transfer Pump G20

**20  
GPM**  
76 L/min

**12V  
DC**  
**Mobile**

### QUICK-FIT MODULAR!

- Easily attach a filter, meter or both to build your own custom system
- Simple four-bolt connections can be mounted in multiple directions

Automatic or Manual  
Nozzle Models  
available

Strainer Access:  
Easy Maintenance

Lockable  
Nozzle  
Holder



Class 1, Div 2  
PO = Class 1, Div 1



**» GPI EXCLUSIVE!**  
Factory-Installed Power Cord:  
Reduced Installation Time

Spin Collar Mount:  
Easy Installation and Pump Orientation

The first gear pump to deliver  
**TRUE 20 GPM** with a 14 ft.  
hose and automatic nozzle.

### DIECAST ALUMINUM HOUSING

- Lightweight - weighs 19 lbs. - low stress on tank

### ROTARY GEAR DESIGN

- Fewer moving parts = less friction and less wear on components
- Minimal maintenance and longer pump life

### ELECTRICAL

Input: 12V (dc) w/40 amp circuit breaker switch

Type: Rotary Gear

Current Draw: 34 amps

Motor: 2000 RPM, .38 HP,  
UL Listed to US and Canadian Standards

### PERFORMANCE

Flow Rate: 20 GPM (76 L/min)

Duty Cycle: 30 min. ON,  
30 min. OFF

### OPERATING PRESSURE

12 psi (0.82 bar) - Standard Pressure

### OPERATING TEMPERATURE

-22°F to 131°F (-30°C to 55°C)

### PUMP HOUSING

Corrosion-Resistant Diecast Aluminum

### MECHANICAL CONNECTIONS

Inlet / Outlet: 1 in. NPT

Mounting: 2 in. NPT

### DISPENSING HOSE

14 ft. (4.2 m) x 1 in.

### SUCTION PIPE

Telescoping 15 to 40 in.  
(38.1 to 101.6 cm)

### POWER CORD

18 ft. (5.5 m), 12/2 AWG

### WARRANTY

Limited Lifetime\* (Pump)

### > Compatible Fluids

Designed, tested and approved for use with gasoline blends (up to E15), diesel fuel blends (up to B20) and kerosene.

### > Pump Only Models

Additional compatible fluids: pump only models also support the use of aviation gasoline (AVGAS100LL) and kerosene grade (JET A).

\*Extended warranty coverage requires registration with GPI.  
Default warranty is 2 years. Visit [gpi.net/product-registration/](http://gpi.net/product-registration/)

# QUICK-FIT READY!

Mount accessories in multiple directions with the **90 Degree Outlet** (Part #162205-01)

Quickly attach a filter, meter, or both to customize your personal fuel station.

**+ EASILY ADD A FUEL FILTER**

**QUICK-FIT FILTER ADAPTER KIT**

Part#129500-01

See page 14

**⊘ CLEAN AND SIMPLE!**  
No pipe fittings, tape, or sealant required for installation

**+ EASILY ADD A FUEL METER**

**M30 MECHANICAL FUEL METER**

Part#165100-01 (Gallons)  
or #165100-02 (Litres)

See page 37

LEARN MORE

**QUICK-FIT PRODUCT GUIDE** [page 15](#)



## > Ordering Information

	Part No.	Model	Nozzle	Hose	Power Cord	Mount	Suction Pipe	Nozzle Holder
<b>a</b>	162000-03	G20-012AD	Automatic	14 ft.	Installed	Spin Collar	Included	Lockable
<b>b</b>	162000-02	G20-012MD	Manual	14 ft.	Installed	Spin Collar	Included	Lockable
<b>c</b>	162000-01	G20-012PO	None	None	None	Spin Collar	None	Lockable