



IDEAL FOR USE WITH HOSE REEL

# GPRO<sup>®</sup> PROFESSIONAL GRADE > Fuel Transfer Pump

# V25-012

**25**  
**GPM**  
94 L/min

**12V**  
**DC**  
**Mobile**

### Quick-Fit Modular!

- Just four bolts and an O-ring for fast, leak-free installation of Quick-Fit Modular accessories

Multi-Directional  
90° Outlet

### » GPRO EXCLUSIVE!

Factory-Installed Power Cord: Reduced Installation Time

### Internal Check Valve with "Perfect Prime"

- Keeps pump head primed and ready  
- Reduces wear by avoiding dry prime conditions

Easy Access to Fuel Strainer

### Tank Adapter Included

- Easy Installation  
- Ready for anti-siphon  
- Vent kit sold separately



Class 1, Div 2  
PO = Class 1, Div 1

Equipped with

**SAFE STOP**

- 30-Minute, Auto Power Down with Easy Reset
- Pump 750 Gallons Uninterrupted
- Prevents Misuse

- Field replaceable switch and circuit breaker
- Switch actuator is diecast solid aluminum construction = no more broken switches
- NEW molded coverplate seal keeps moisture out and stays in place

### ELECTRICAL

Input:	12V (dc) w/40 amp circuit breaker switch
Type:	Carbon Vane
Current Draw:	35 amp
Motor:	2000 RPM, 4/10 HP, UL Listed to US and Canadian Standards

### PERFORMANCE

Flow Rate: 25 GPM (94 L/min)

Duty Cycle: 30 min. ON, 30 min. OFF

### OPERATING PRESSURE

20 psi (1.38 bar) - High Pressure

### OPERATING TEMPERATURE

-20°F to 125°F (-29°C to 52°C)

### PUMP HOUSING

Powder Coated Cast Iron

### MECHANICAL CONNECTIONS

Inlet / Outlet: 1 in. NPT

Mounting: 2 in. NPT

### DISPENSING HOSE

18 ft. (5.5 m) x 1 in.

### SUCTION PIPE

1 in. NPT, Telescoping to 40 in. (101.6 cm)

### POWER CORD

18 ft. (5.5 m), 10/2 AWG

### WARRANTY

5 Year Pump







**a** V25-012AD  
V25-012AD+XT  
V25-024AD



**b** V25-012MD  
V25-024MD



**c** V25-012PO  
V25-012PO+XT  
V25-024PO

- Powder coating creates a durable and long-lasting finish that resists corrosion, withstands chipping, scratching, fading, and wearing
- Extreme Temperature Series (XT) models available -

*Capable of operation in temperatures as low as -40°F (-40°C)*

# GPRO®

## PROFESSIONAL GRADE

> Fuel Transfer Pump

**25**  
**GPM**  
94 L/min

**24V**  
**DC**  
**Mobile**

# V25-024



Class 1, Div 2  
PO = Class 1, Div 1

ELECTRICAL		PUMP HOUSING	
Input:	24V (dc)	Powder Coated Cast Iron	
Type:	Carbon Vane	MECHANICAL CONNECTIONS	
Current Draw:	20 amp	Inlet / Outlet:	1 in. NPT
Motor:	2000 RPM, 4/10 HP, UL Listed to US and Canadian Standards	Mounting:	2 in. NPT
PERFORMANCE		DISPENSING HOSE	
Flow Rate:	25 GPM (94 L/min)	18 ft. (5.5 m) x 1 in.	
Duty Cycle:	30 min. ON, 30 min. OFF	SUCTION PIPE	
<b>OPERATING PRESSURE</b>		1 in. NPT, Telescoping to 40 in. (101.6 cm)	
20 psi (1.38 bar) - High Pressure		POWER CORD	
<b>OPERATING TEMPERATURE</b>		18 ft. (5.5 m), 10/2 AWG	
-20°F to 125°F (-29°C to 52°C)		WARRANTY	
		5 Year Pump	

### > Ordering Information

	Part No.	Model	Nozzle	Hose	Power Cord	Suction Pipe	Temperature Rating
12V	<b>a</b> 170000-03	V25-012AD	Automatic	18 ft.	Installed	Included	-20° F (-29° C)
	<b>b</b> 170000-02	V25-012MD	Manual	18 ft.	Installed	Included	-20° F (-29° C)
	<b>c</b> 170000-01	V25-012PO	None	None	None	None	-20° F (-29° C)
	<b>a</b> 170000-06	V25-012AD+XT	Automatic	18 ft.	Installed	Included	Tested to -40° F (-40° C)
	<b>c</b> 170000-05	V25-012PO+XT	None	None	None	None	Tested to -40° F (-40° C)

24V	<b>a</b> 170001-03	V25-024AD	Automatic	18 ft.	Installed	Included	-20° F (-29° C)
	<b>b</b> 170001-02	V25-024MD	Manual	18 ft.	Installed	Included	-20° F (-29° C)
	<b>c</b> 170001-01	V25-024PO	None	None	None	None	-20° F (-29° C)

### > Compatible Fluids

*Designed, tested and approved for use with gasoline blends (up to E15), diesel fuel blends (up to B20) and kerosene.*

### > Pump Only Models

*Additional compatible fluids: pump only models also support the use of aviation gasoline (AVGAS100LL) and kerosene grade (JET A).*