



P-200-2UR

8 GPM
30 L/min

12V DC

Current Draw: 24 amps

Motor: 3250 RPM, 1/4 HP

POWER CORD

15 ft. (4.6 m),
10 AWG

MAX VISCOSITY

450 CPS



PA-200-2UR

8 GPM
30 L/min

115V AC

Current Draw: 3 amps

Motor: 3250 RPM, 1/4 HP

POWER CORD

18/3 AWG with
grounded plug

MAX VISCOSITY

450 CPS



> Lightweight Oil Transfer Pumps

- Designed specifically for use with thin to medium viscosity petroleum fluids and up to 30W oil
- Lightweight design is easy to move between barrels or drums

For use with: *Non-flammable oil-based solvents. Do not use with gasoline, diesel fuel or waste oil.*



SPECIAL APPLICATION PUMPS



ELECTRICAL

Type: Gear

PERFORMANCE

Duty Cycle: 30 min. ON,
30 min. OFF

OPERATING PRESSURE

16 psi (1.10 bar)

OPERATING TEMPERATURE

-20°F to 120°F (-29°C to 50°C)

PUMP HOUSING

Polypropylene

MECHANICAL CONNECTIONS

Inlet/Outlet: 1 in. NPT

Mounting: 2 in. NPT

DISPENSING HOSE

12 ft. (3.7 m) x 1 in.

SUCTION PIPE

Telescoping 15 to 40 in.
(38.1 to 101.6 cm)

WARRANTY

2 Year Pump



a P-200-2UR



b PA-200-2UR

> Ordering Information

	Part No.	Model	Voltage	Power Cord
a	118000-9	P-200-2UR	12V (dc)	15 ft. (4.6 m)
b	118003-11	PA-200-2UR	115V (ac)	3 ft. (.91 m)

*Rate and duty cycle will vary with viscosity and temperature

