

GORILLA



Product Specification

Application

A premium-quality, multipurpose industrial hose with a wide range of applications in factories, construction, agriculture, quarries, mines, railroads, the oil and gas industry and shipbuilding. All sizes are crush-resistant and rated at 500 psi (3.4 MPa) maximum working pressure. The premium Carbryn™ cover offers the most superior abrasion resistance of air and multipurpose hoses. Non-conductive, minimum electrical resistance greater than 1 megohm per inch of hose length at 1000 Volts DC.

Construction Tube

- Nitrile Synthetic Rubber, ARPM Class A (High Oil Resistance)

Cover

- Yellow Carbryn™ Synthetic Rubber, ARPM Class A (High Oil Resistance) (MSHA Approved)

Reinforcement

- Spiral Flexten® Yarn, 2" is Braided S

Temperature Range

- 20 F / -29 C ~ 190 F / 88 C

Design Factor

- 4:1

Packaging

3/16" – 3/4"	500' reels, maximum 3 pieces, 50' increments
1"	450' reels, maximum 3 pieces, 50' increments
1-1/4"	250'–400' reels, maximum 3 pieces, 50' increments
1-1/2"	150'–300' reels, maximum 3 pieces, 50' increments
2"	200' carton, maximum 3 pieces, 50' increments

Coupled assemblies available: 1/4", 3/8", 1/2", and 3/4".

Branding

Gorilla® 1" (25.4 mm) 500 PSI. Made in USA. Continental Flame Resistant USMSHA No. 2G-IC-14C/39

Coupling

*Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.
*(Ready 2 Go logo)
- Coupled assemblies available.


Non Stock / Sizes

For special production run minimum requirements, see Appendix D.

GORILLA

Order Codes: 569-035 (1/4" - 1 1/2"), 536-446 (2")

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	Packaging	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/4	6.40	0.61	15.50	500	Yellow	Reel	500	3.45	0.17	0.25	20026239
5/16	7.94	0.69	17.50	500	Yellow	Reel	500	3.45	0.20	0.30	20026255
3/8	9.53	0.73	18.60	500	Yellow	Reel	500	3.45	0.22	0.33	20026256
1/2	12.70	0.89	22.60	500	Yellow	Reel	500	3.45	0.28	0.42	20026273
				500	Yellow	CCT	500	3.45	0.28	0.42	20917330
5/8	15.88	1.06	26.90	500	Yellow	Reel	500	3.45	0.35	0.52	20026289
3/4	19.10	1.19	30.20	500	Yellow	Reel	500	3.45	0.41	0.61	20026290
1	25.40	1.50	37.80	450	Yellow	Reel	500	3.45	0.58	0.86	20026304
1-1/4	31.80	1.77	45.60	400	Yellow	Reel	500	3.45	0.79	1.18	20026306
1-1/2	38.10	2.04	51.80	300	Yellow	Reel	500	3.45	0.86	1.27	20026309
2	50.80	2.62	66.60	50	Yellow	Carton	500	3.45	1.22	1.82	20305356
				100	Yellow	Carton	500	3.45	1.22	1.82	20023183

GORILLA READY 2 GO


ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Coupled Ends	WP (PSI)	WP (MPa)	Part Number
1/4	6.40	0.61	15.50	25	Yellow	MxM 1/4 NPT	500	3.45	20129563
				50	Yellow	MxM 1/4 NPT	500	3.45	20132763
3/8	9.53	0.73	18.60	25	Yellow	MxM 3/8 NPT	500	3.45	20129566
				50	Yellow	MxM 3/8 NPT	500	3.45	20132764
1/2	12.70	0.89	22.60	25	Yellow	MxM 1/2 NPT	500	3.45	20129569
				50	Yellow	MxM 1/2 NPT	500	3.45	20132766
3/4	19.10	1.19	30.20	50	Yellow	MxM 3/4 NPT	500	3.45	20129582
				50	Yellow	Universal	500	3.45	20129683